




CHMER EDM

Electric Discharge Machine



Rising Star Award



National Award



IT'S VERY WELL
MADE IN TAIWAN

CM H32Z DRILLING E.D.M



CM H32Z

CHING HUNG MACHINERY & ELECTRIC INDUSTRIAL CO., LTD.

CM H32Z

FEATURES:

- Drill small diameter holes through hardened tool steel and carbide.
- Depth to diameter ratios >100(i.e., .020 dia. >2" deep.)
- Enter on curved or angled surfaces.
- Dielectric is distilled water.
- 3-axis DROs.
- Edge finding and hole center finding.
- Inch/metric switchable.
- Z depth programmable.
- 99 built-in power settings plus operator programmed power settings (s-codes).

OPTION :

- ER Spindle

- CE Conformity

STANDARD ACCESSORIES DELIVERED WITH THE MACHINE:

- GUIDE Dia. 1.0 mmx1
- ELECTRODE BRASS Tube Dia. 1.0X400 mmx10
- INSERT RUBBERS Dia. 1.0 mmx3
- GUIDE Dia. 0.5mmx1
- INSERT RUBBERS Dia. 0.5 mmx3
- ELECTRODE BRASS Tube Dia. 0.5X400 mmx10
- TOOL BOXx1
- PAINT SPAREx1

- MACHINE PADx3
- FLUSHING PIPEx1
- FILTERx1
- FLUSHING NOZZLEX1
- AIR FAST CONNECTORx1
- SET OF ALLEN SPANNERx1
- HANDLE FOR FILTERCAPx1

SPECIFICATION :

Max. Work Piece (WxDxH)	mm / inch	800x400x300 / 31.4x15.7x11.8
Max. Work Piece Weight	kg / lb	200 / 440
Table travels (XxY)	mm / inch	350 x 250 / 13.7x9.8
Ram Servo Travel (Z1)	mm / inch	340 / 13.3
Work Head Travel (Z2)	mm / inch	200 / 7.8
Guide Travel	mm / inch	150 / 5.9
Max. Length of Tube Electrode	mm / inch	400 / 15.7
Distance between Spindle Platen to Work Table	mm / inch	5-400 / 0.2-15.7
Machine Size	mm / inch	1380x1000x2350 / 54.3x39.3x92.5
Net Weight	kg / lb	800 / 1760

POWER UNIT :

Input Power	3 KVA
Pulse Generation	Power fet switching
Current	47 Amps
Current Channels	9 steps
Pulse Width	10 steps / each
Input voltage	220 / 440 3ph/60Hz

※ Note : The manufacturer reserves the right to modify the design, specifications, mechanisms.....etc. to improve the performance of the machine without notice, all the specifications shown above are just for reference.



CHING HUNG MACHINERY & ELECTRIC INDUSTRIAL CO., LTD.

No.28, LANE 229 SEC.1, CHUNG SHANG ROAD, WUJIH HSIANG, TAICHUNG HSIEN, TAIWAN, R.O.C.

TEL: 886-4-23373515 URL: <http://www.chmer.com>

FAX: 886-4-23370718 E-mail: overseas@mail.chmer.com

Distributed by:

S5B-0032A